

THE PERFECT COST EFFECTIVE VALIDATION SYSTEM

- **Hygienic Design**
- **Non Invasive External Sensor**
- **Standard Tri Clamp Fixing**
- **Simple Signal Output**
- **Reduced Contamination**
- **No Electronics Inside**
- **Easy to Update/Install**
- **Links Straight Into Common Feedback Circuits. AS-i Compatible**

Versatile & Unique

The Veri-Clean validation system uses a high sensitivity magnetic sensor to detect rotational forces of a special PTFE encapsulated target linked to the Typhoon tank washer. The sensor is mounted totally externally to the tank, isolating any cleaning fluid or solvent from any electronics. All moving parts are lubricated by the cleaning fluid and the complete sensor housing is made from 316L stainless steel. All bearing materials can be either Pure PTFE for FDA or Carbon Filled PTFE for ATEX applications.

Applications

The Veri-Clean system is ideally suited to applications where an automated signal indicating that the tank cleaning device is working correctly is required. The system is designed to work with the Typhoon tank washer in the brewing, beverage, food, chemical, biotech and pharmaceutical industries. The neat, compact design makes it easy to retrofit to existing typhoon units, or simple to install as new project.

Operation

Inside the sensor housing a PTFE encapsulated, magnet rotates as the cleaning head rotates. This target is detected by the external sensor. A simple positive/negative pulse feed is generated. This signal can be wired into a PLC type control system, a simple signal indicator or other system. The unit can also plug directly into an AS-i ring circuit and link back to an AS-i control console.

BRECONCHERRY SELLERSCLEAN

International specialists in the design and
manufacture of tank cleaning equipment

Australia & New Zealand Distributor:



TECHNICAL PROJECTS

DNL OF MATHI PRODUCTS PTY. LTD A.B.N. 83 090 115 476

4/44 Carrington Road
Castle Hill NSW 2154
Australia

Tel: +61 (0)2 9634 3370
Fax: +61 (0)2 9634 6418
Email: sales@tecpro.com.au
Web: www.tecpro.com.au



We reserve the right to change specification
without notice. Whilst we endeavour to provide
accurate up to date information, all information
is provided as a guide only.

"Breconcherry", "Veri-Clean" are internationally
registered trade marks of Breconcherry Limited.
Copyright © Breconcherry Limited 1999

Maintenance & Inspection

The low wear design requires minimal maintenance. Any spare parts, technical assistance or repair facilities required can be obtained through the global Breconcherry distributor network. As with all mechanical devices, it is recommended that the unit be regularly inspected for correct operation.


Minimum Manhole/Flange Size

The minimum Tri clamp connection size required for the unit is 2".

Technical Data

Materials of Construction:	Stainless Steel 316/316L, PTFE, C-PTFE, PEEK, Hastelloy
Max. Operating Temperature:	100° Centigrade
Max. Ambient Temperature:	140° Centigrade
Standard Connections:	2" Tri Clamp
Sensor Type:	Magnetic Proximity IP68/69K
Power Supply:	24VDC@100mA

Assembly Example



For optimal efficiency use a pre-filter or strainer to prevent particulate clogging.