

COMPLEMENTARY PRODUCTS

UMV

The UMV series washgun has been designed primarily to avoid hot water waste, while assuring very comfortable operation conditions.

Its thick rubber lining not only effectively protects the operator hands from the discomfort of hot water temperature, but also assures an excellent protection in case the washgun is dropped or falls to the ground

since it avoids any damage to the tiles or the equipment.

The careful design, thought for the food industry, also includes a rubber quality resisting greases and usual detergents, plus a blue color chosen to give immediate visibility against a white/clear foreground.

The trigger is lined too with rubber, and can be hold in the open position by means of a lock ring.


The spray pattern can be adjusted continuously between a closed straight jet to a wide angle spray, so that the proper spray pattern can be chosen for each single job.

Materials

Body	T2	Brass casting chrome plated
Lining	P8	EPDM
Stem	B3	Aisi 316 stainless steel
Trigger	B3	Aisi 316 stainless steel, rubber lined

Connection	13	mm	hose fitting
Weight	0.9	kg	
Max temperature	95	°C	
Max pressure	24	bar	

WATER GUNS



UMV 2210 T2

The versatility of this washgun is enhanced from the additional model UMV 2211 T8 , which can be fitted with additional lances.

The two different lance models are easily fitted to the gun body with a 1/2" male nipple. and offer the following choice of operation

1
Foaming machines and equipment foaming prior to washing

The foam lance comes with a quick connect female coupling, and a matching coupling must be fitted at the gun outlet.

2
General purpose 1/4" fem thread outlet, 1/4" male thread inlet. Available both with heat protection sleeve, or bare zinc-plated steel.

The general purpose lance needs a connection nipple 1/4" fem to 1/2" male to be fitted on the gun. Please see the complete washgun and components codes below.

Complete guns

UMV 2210 T2	Standard, adjustable jet
UMV 220A T2	With foam lance
UMV 220B T2	With 1/4" fem outlet, bare lance
UMV 220C T2	With 1/4" fem outlet, heat protected lance

Components

UMV 2211 T2	Washgun with 1/2" female thread, without lance
XUM V001 B3	Foam lance
XUM V002 B3	Quick connect coupling for foam lance, 1/2" m
XUM V003 B3	Universal lance, 1/4" fem outlet, with heat protection
XUM V004 B3	Universal lance, 1/4" fem outlet, bare zinc-plated steel
XUM V005 T2	Chrome plated brass nipple (1/4" f / 1/2" m)



UMV 2211 T2 + XUM V002 B3 + XUM V001 B3 =

UMV 220A T2

+ XUM V005 T8 + XUM V004 B3 =

UMV 220B T2

+ XUM V005 T8 + XUM V003 B3 =

UMV 220C T2